



N=Number of contacts



P.C.B. LAYOUT



SIGN	DESCRIPTION	DATE	APPROVER

Technical Data:
 Material:
 Wire guard : stainless steel
 Surface of solder tail : Copper Alloy Tin plated
 Insulator body(housing) : Polyamide(Glass filled)(UL94V-0)
 Electrical
 Voltage rating: 150VAC
 Current rating: 2 Amps/way max
 Contact resistance: 20mΩ(max)
 Withstanding Voltage: 2000VAC(1min) Test time=60sec/1pcs
 Wire Range:20-26Awg
 Mechanical:
 Operating temperature: -40°C to +105°C
 Soldering reliability:
 Test temperature= 250°C±10°C
 5 seconds max
 Ordering Information:
 F50 - 21 - 2 XX - 0 0 X 0

2	02	5	Green
-	-	6	Blue
24	24	8	Grey
		A	Black

WELINK 上海拓尔普电子科技有限公司
 Welink International Co.,LTD.

TOLERANCE	APPROVED:	NAME: F5021 - pitch 2.5mm
X: ±0.50	CHECKED:	- series
X.X ±0.30	DRAWN: Yang Ming 2012,06,20	
X.XX ±0.20	UNITS: mm	PART NO: F50212XX00X0
X° ±1°	REV: A	DWG NO: 9F5021201A
⊕	SCALE: 3 / 1	PAGE: 1 / 1